

Definition

Random variable (R.V.) X: A function on sample space $\Box X: S \to R$ Cumulative distribution function (CDF): Probability distribution function (PDF) Distribution function $\Box F_{x}(x) = P(X < x)$ Probability density function (pdf): Used for continuous R.V. $F_X(x) = \int_{-\infty}^x f_X(t) dt$ $f_X(x) = \frac{dF_X(x)}{dx}$

Two Classes of R.V.

Discrete R.V.

- Bernoulli
- Binomial
- Geometric
- Poisson

Continuous R.V.

- Uniform
- Exponential, Erlang
- Normal

- Closely related
 - \Box Exponential $\leftarrow \rightarrow$ Geometric
 - □ Normal \leftarrow → Binomial, Poisson

Bernoulli

 A trial/experiment, outcome is either "success" or "failure".
 X=1 if success, X=0 if failure
 P(X=1)=p, P(X=0)=1-p
 Bernoulli Trials
 A series of independent repetition of Bernoulli trial.

Binomial

A Bernoulli trials with n repetitions \square Binomial: X = No. of successes in n trails $\Box X \sim B(n, p)$ $P(X = k) \equiv f(k; n, p) = \binom{n}{k} p^k (1-p)^{n-k}$ where $\binom{n}{k} = \frac{n!}{(n-k)!k!}$ p=0.5 and n=20 p=0.7 and n=20 p=0.5 and n=40 0.10 0.05 0.00 0 10 20 30 5 UCF Stands For Opportunity IOOL OF FLECTRICAL ENGINEERING & COMPUTER SCI

Binomial Example

- A communication channel with (1-p) being the probability of successful transmission of a bit. Assume we design a code that can tolerate up to e bit errors with n bit word code.
- Q: Probability of successful word transmission?
- Model: sequence of bits trans. follows a Bernoulli Trails
 - Assumption: each bit error or not is independent
 - \square P(Q) = P(e or fewer errors in n trails)

$$= \sum_{i=0}^{e} f(i; n, p)$$
$$= \sum_{i=0}^{e} \binom{n}{i} p^{i} (1-p)^{n-i}$$

Geometric

- Still about Bernoulli Trails, but from a different angle.
- X: No. of trials until the first success
- Y: No. of failures until the first success
 P(X=k) = (1-p)^{k-1}p
 P(Y=k)=(1-p)^kp



UCF

Stands For Opportunity

7



Continous R.V - Uniform

• X: is a uniform r.v. on (α, β) if

$$f(x) = \begin{cases} \frac{1}{\beta - \alpha}, & \text{if} \alpha < x < \beta \\ 0 & \text{otherwise} \end{cases}$$

 Uniform r.v. is the basis for simulation other distributions
 Introduce later

Exponential

• r.v. X: $f(x) = \begin{cases} \lambda e^{-\lambda x}, & \text{if } x \ge 0 \\ 0 & \text{if } x < 0 \end{cases}$ • $F_X(x) = 1 - e^{-\lambda x}$

Very important distribution
 Memoryless property
 Corresponding to geometric distr.



Erlang

• r.v. X (k-th Erlang): $f(x;k,\lambda) = \frac{\lambda^k x^{k-1} e^{-\lambda x}}{(k-1)!} \quad \text{for } x, \lambda \ge 0.$

K-th Erlang is the sum of k Exponential distr.



Normal

□ **r.v.** X:

$$f(x) = \frac{1}{\sqrt{2\pi\sigma}} e^{-(x-\mu)^2/2\sigma^2}, -\infty < x < \infty$$

Corresponding to
 Binomial and Poisson
 distributions



Normal

If X~N(μ, σ²), then
r.v. Z=(X-μ)/σ follows standard normal N(0,1)
P(Z<x) is denoted as Φ(x)
Φ(x) value can be obtained from standard normal distribution table (next slide)
Used to calculate the distribution value of a normal random variable X~N(μ, σ²)
P(X<α) = P(Z < (α-μ)/σ) = Φ((α-μ)/σ)

Standard Normal Distr. Table



	P(X < x)	$=\Phi$	(x)	
--	----------	---------	-----	--

 $\Box \Phi(-\mathbf{x}) = 1 - \Phi(\mathbf{x}) \text{ why?}$

z	F(X)	Z	F(X)	Z	F (X)
-2.5	0.006	-1	0.159	0.5	0.691
-2.4	0.008	-0.9	0.184	0.6	0.726
-2.3	0.011	-0.8	0.212	0.7	0.758
-2.2	0.014	-0.7	0.242	0.8	0.788
-2.1	0.018	-0.6	0.274	0.9	0.816
-2	0.023	-0.5	0.309	1	0.841
-1.9	0.029	-0.4	0.345	1.1	0.864
-1.8	0.036	-0.3	0.382	1.2	0.885
-1.7	0.045	-0.2	0.421	1.3	0.903
-1.6	0.055	-0.1	0.46	1.4	0.919
-1.5	0.067	0	0.5	1.5	0.933
-1.4	0.081	0.1	0.54	1.6	0.945
-1.3	0.097	0.2	0.579	1.7	0.955
-1.2	0.115	0.3	0.618	1.8	0.964
-1.1	0.136	0.4	0.655	1.9	0.971

- About 68% of the area under the curve falls within 1 standard deviation of the mean.
- About 95% of the area under the curve falls within 2 standard deviations of the mean.
- About 99.7% of the area under the curve falls within 3
 - standard deviations of the mean.

Normal Distr. Example

- An average light bulb manufactured by Acme Corporation lasts 300 days, 68% of light bulbs lasts within 300+/- 50 days. Assuming that bulb life is normally distributed.
 - Q1: What is the probability that an Acme light bulb will last at most 365 days?
 - Q2: If we installed 100 new bulbs on a street exactly one year ago, how many bulbs still work now? What is the distribution of the number of remaining bulbs?

Step 1: Modeling

- □ $X \sim N(300, 50^2)$ $\mu=300, \sigma=50$. Q1 is P(X ≤ 365) define Z = (X-300)/50, then Z is standard normal
- For Q2, # of remaining bulbs, Y, is a Bernoulli trial with 100 repetitions
 - Y follows Binomial distribution (approximate to normal distr.)

 \square Y ~ N(np, np(1-p)) refer to Wikipedia

Memoryless Property

- Memoryless for Geometric and Exponential
 Easy to understand for Geometric
 - Each trial is independent → how many trials before hit does not depend on how many times I have missed before.

• X: Geometric r.v., $P_X(k)=(1-p)^{k-1}p$;

Y: Y=X-n No. of trials given we failed first n times

$$P_{Y}(k) = P(Y=k|X>n)=P(X=k+n|X>n)$$

$$P(X=k+n,X>n) = P(X=k+n,X>n)$$

$$= \frac{(1-p)^{k+n-1}p}{(1-p)^n} = p(1-p)^{k-1} = P_X(k)$$

pdf: probability density function Continuous r.v. f_x(x) pmf: probability mass function Discrete r.v. X: P_x(x)=P(X=x) Also denoted as p_x(x) or simply p(x)

Mean (Expectation)

- Discrete r.v. X
 E[X] = ∑ kP_X(k)
 Continous r.v. X
 E[X] = ∫[∞]_{-∞} kf(k)dk
- □ Bernoulli: $E[X] = O(1-p) + 1 \cdot p = p$
- Binomial: E[X]=np (intuitive meaning?)
- □ Geometric: E[X]=1/p (intuitive meaning?)
- Poisson: $E[X] = \lambda$ (remember $\lambda = np$)

Mean

Continuous r.v.
 Uniform: E[X]= (α+β)/2
 Exponential: E[X]= 1/λ
 K-th Erlang E[X] = k/λ
 Normal: E[X]=μ

Function of Random Variables

R.V. X, R.V. Y=g(X)
Discrete r.v. X:
□ E[g(X)] = ∑ g(x)p(x)
Continuous r.v. X:
□ E[g(X)] = $\int_{-\infty}^{\infty} g(x)f(x)dx$

 Variance: Var(X) = E[(X-E[X])²] = E[X²] - (E[X])²

Joint Distributed Random Variables

F_{XY}(x,y)=P(X≤ x, Y≤ y)
F_{XY}(x,y)=F_X(x)F_Y(y) independent
F_{X|Y}(x|y) - F_{XY}(x,y)/F_Y(y)
E[α X +β Y]=α E[X]+β E[Y]
If X, Y independent

E[g(X)h(Y)]=E[g(X)]· E[h(Y)]

Covariance
Measure of how much two variables change together

$$\Box Cov(X,Y)=E[(X-E[X])(Y-E[Y])]$$
$$= E[XY] - E[X]E[Y]$$

• If X and Y independent, Cov(X,Y)=0

Limit Theorems - Inequality

Markov's Inequality \Box r.v. X \geq 0: $\forall \alpha > 0$, P(X $\geq \alpha) \leq E[X]/\alpha$ Chebyshev's Inequality \Box r.v. X, E[X]= μ , Var(X)= σ^2 \square \forall k>0, P(|X- μ |> k)< σ^2/k^2 Provide bounds when only mean and variance known The bounds may be more conservative than derived bounds if we know the distribution

Inequality Examples

• If $\alpha = 2E[X]$, then $P(X \ge \alpha) \le 0.5$

- A pool of articles from a publisher. Assume we know that the articles are on average 1000 characters long with a standard deviation of 200 characters.
- Q: what is the prob. a given article is between 600 and 1400 characters?
- □ Model: r.v. X: μ =1000, σ =200, k=400 in Chebyshev's
- □ $P(Q) = 1 P(|X \mu| \ge k)$ $\ge 1 - (\sigma/k)^2 = 0.75$
- If we know X follows normal distr.:
 75% chance of an article being between 770 and 1230 characters long

Strong Law of Large Number

i.i.d. (independent and identically-distributed)
 X_i: i.i.d. random variables, E[X_i]=µ

With probability 1, $(X_1+X_2+\dots+X_n)/n \rightarrow \mu$, as $n \rightarrow \infty$

Foundation for using large number of simulations to obtain average results

Central Limit Theorem

- X_i: i.i.d. random variables, $E[X_i] = \mu Var(X_i) = \sigma^2$ • Y= $\frac{X_1 + X_2 + \dots + X_n - n\mu}{\sigma\sqrt{n}}$
- □ Then, Y ~ N(0,1) as n→∞
 □ The reason for why normal distribution is everywhere

• Sample mean $\bar{X} = \sum_{i=1}^{n} X_i/n$ $E[\bar{X}] = \mu$ $Var(\bar{X}) = \sigma^2/n$



□ Let X_i , i=1,2,..., 10 be i.i.d., X_i is uniform distr. (0,1). Calculate $P(\sum_{i=1}^{10} X_i > 7)$

 \Box E[X_i]=0.5, Var(X_i)=1/12

$$P(\sum_{i=1}^{10} X_i > 7) = P(\frac{\sum_{i=1}^{10} X_i - 5}{\sqrt{10(1/12)}} > \frac{7 - 5}{\sqrt{10(1/12)}})$$

 $\approx 1 - \Phi(2.2) = 0.0139$ $\Phi(x)$: prob. standard normal distr. < x

Conditional Probability

Suppose r.v. X and Y have joint pmf p(x,y)
 p(1,1)=0.5, p(1,2)=0.1, p(2,1)=0.1, p(2,2)=0.3
 Q: Calculate the pmf of X given that Y=1

• Similarly, $p_{X|Y}(2,1) = 1/6$

Expectation by Conditioning

- r.v. X and Y. then E[X|Y] is also a r.v.
 Formula: E[X]=E[E[X|Y]]
 Make it clearer, E_x[X]=E_y[E_x[X|Y]]
 - □ It corresponds to the "law of total probability" □ $E_X[X] = \sum E_X[X|Y=y] \cdot P(Y=y)$

Used in the same situation where you use the law of total probability

• r.v. X and N, independent • $Y=X_1+X_2+\cdots+X_N$

Q: compute E[Y]?

- A company's network has a design problem on its routing algorithm for its core router. For a given packet, it forwards correctly with prob. 1/3 where the packet takes 2 seconds to reach the target; forwards it to a wrong path with prob. 1/3, where the packet comes back after 3 seconds; forwards it to another wrong with prob. 1/3, where the packet comes back after 5 seconds.
- Q: What is the expected time delay for the packet reach the target?
 - Memoryless
 - Expectation by condition

- Suppose a spam filter gives each incoming email an overall score. A higher score means the email is more likely to be spam. By running the filter on training set of email (known normal + known spam), we know that 80% of normal emails have scores of 1.5 ± 0.4 ; 68% of spam emails have scores of 4 ± 1 . Assume the score of normal or spam email follows normal distr.
- Q1: If we want spam detection rate of 95%, what threshold should we configure the filter?
- Q2: What is the false positive rate under this configuration?

- A ball is drawn from an bottle containing three white and two black balls. After each ball is drawn, it is then placed back. This goes on indefinitely.
 - Q: What is the probability that among the first four drawn balls, exactly two are white?

$$P(X = k) \equiv f(k; n, p) = \binom{n}{k} p^k (1-p)^{n-k}$$

- A type of battery has a lifetime with μ=40 hours and σ=20 hours. A battery is used until it fails, at which point it is replaced by a new one.
 - Q: If we have 25 batteries, what's the probability that over 1100 hours of use can be achieved?
 Approximate by central limit theorem

- If the prob. of a person suffer bad reaction from the injection of a given serum is 0.1%, determine the probability that out of 2000 individuals (a). exactly 3 (b). More than 2 individuals suffer a bad reaction?
 - (c). If we inject one person per minute, what is the average time between two bad reaction injections?
 - Poisson distribution (for rare event in a large number of event series)

Can use Binomial, but too much computation

Geometric

- A group of n camping people work on assembling their individual tent individually. The time for a person finishes is modeled by r.v. X.
 - Q1: what is the PDF for the time when the first tent is ready?
 - Q2: what is the PDF for the time when all tents are ready?

Suppose X_i are i.i.d., i=1, 2, …, n
 Q: compute PDF of r.v. Y and Z where

 Y= max(X₁, X₂, …, X_n)
 Z= min(X₁, X₂, …, X_n)
 Y, Z can be used for modeling many phenomenon

 (textbook #23 on Page 169)
 A coin having probability p of coming up heads is flipped until two of the most recent three flips are heads. Let N denote the number of heads. Find E[N].

0 0 0 1 0 0 0 1 0 0 1 0 1 0 1 $P(N=n) = P(Y_2 \ge 3, \dots, Y_{n-1} \ge 3, Y_n \le 2)$